



RCS Incubator Hood

Description

This portable RCS incubator hood is ideal for all small-scale incubator applications.

Suitable for:

- Shaker
- Magnetic Stirrer ...
- Temperature sensitive equipments with maximum dimensions of 69 x 65,5 x 61 cm (W x D x H)

Specifications

- Controlled by microprocessors
- Over temperature protection
- Digital display of actual and target values
- Temperature accuracy of $\pm 0,2^{\circ}\text{C}$

Benefits

- A big front panel with self adjustment makes easy to handle and control the installed equipment.
- Acrylic glass is the best material to protect the temperature.
- Constant temperature from ambient up to $+65^{\circ}\text{C}$
- Accuracy $\pm 0,2^{\circ}\text{C}$.
- As an option, we offer a cooling coil system to drop the chamber temperature down to $+8^{\circ}\text{C}$ in reference to the ambient temperature of 20°C (Model UH 4/14).



Option

Cooling Function with Recirculating Chiller Model UH4/14 D

Cooling for Incubators
Cooling capacity up to 250 W
Item No.: 104.0050



UH4/14 Recirculating Chiller

Technical Data

| Model | RCS-550 | RCS-650 | RCS-750 |
|---------------------------------|-----------------------|-----------------------|-----------------------|
| Internal Dimensions (W x D x H) | 49 x 65.5 x 61 cm | 59 x 65.5 x 61 cm | 69 x 65.5 x 61 cm |
| Width of Front Space | 56 + 10.5 cm | 66 + 10.5 cm | 76 + 10.5 cm |
| Aitflow Capacity | 260 m ³ /h | 260 m ³ /h | 260 m ³ /h |
| Power Source | 230 V, 50/60 Hz | 230 V, 50/60 Hz | 230 V, 50/60 Hz |
| Item No. | 104.0250 | 104.0251 | 104.0252 |