



TurboCycler Lite

Description

TurboCycler Lite has a high heating rate, fast boot up, and accurate temperature control. It ensures efficient and accurate PCR processing.

The unit is compact in size and has front-to-back venting which allows machines to be placed side-by-side to save precious bench space.

The monochrome display and touch keypad provide a user friendly interface. All these features make it an ideal solution for growing service centers and the education market while keeping the cost down.



Intuitive Operation Experience

Touch keypad + intuitive graphic interface



Gradient Optimization

The thermal gradient function allows fast PCR optimization for new experiment



Advanced Slow-Ramp Temperature Control

The ramp rate can be precisely controlled down to 0.1 °C/sec to meet the need for the CRISPR/Cas related assays



Fully Adjustable Lid Temperature

The temperature can be set between 35 and 120°C for virtually any type of experiment including NGS pre-treatment



Easy Disinfection

The dust and aerosol proof keypad can be easily disinfected



Auto Restart

Power failure recovery keeps the experiment safe

TurboCycler Lite

Specifications

Sample Block	
Sample Block	Fixed 96-well, compatible with regular profile or low profile 0.2 ml PCR tube, strip, non-skirted, semi-skirted and full-skirted 96-well plate
Sample Volume	10 – 100 µl
Block Temperature	
Temperature Range	4.0 – 99.9 °C
Max. Heating Rate	3.0 °C/sec
Max. Cooling Rate	2.0 °C/sec
Temperature Accuracy	± 0.3 °C
Temperature Uniformity Across Block	± 0.5 °C
Adjustable Ramp Rate	High / Low
Slow-Ramp Temperature Control	Via temperature increment / decrement between cycles
Gradient Temperature	
Gradient Direction	Horizontal across the block
Gradient Temperature Range	30 – 99 °C
Gradient Temperature Difference	Max. span 24 °C
Heated Lid	
Temperature Setting Range	35 – 120 °C or off
Temperature Accuracy	± 1.0 °C
Software	
Stored Program No.	200 sets
Registered User Folder No.	50 sets
User Folder Password Protection	Yes
General	
Display	Monochrome LCM, 240 x 128 pixels
Input Interface	Capacitive touch keypad
Auto Restart after Power Outage	Yes
Footprint Dimensions (H x W x D)	225 x 245 x 415 mm
Weight	9.0 kg
Power Supply	VAC 240 V, 50/60 Hz, 500W
Certification	CE IVD, RoHS